



Machine might vary in reality

## Section 1: Product Specification

### 1.1. Trade name

# LithoPore® Cutting Machine SM100

### 1.2. Manufacturer

LithoPore Europe GmbH

Email: [info@lithopore.com](mailto:info@lithopore.com)

The **LithoPore® Cutting Machine SM100** is a dust free automatic wire cutting machine. It is suitable to cut LithoPore® Aerated Concrete – LPAC up to ~200 kPa of compressive strength.

## Section 2: Advantages at a glance

- Dust free cutting process
- Reduced wastage material due to finer cutting wires
- Fast exchange of wires
- Flexible block design possible

## Section 3: Description

- Pre cutter for top and bottom cutting
- 2 x Main cutter for vertical cutting (longitudinal and transversal)
- Fully-automatic cutting process
- Block height is fixed through mould height
- Flexible block dimension
- Minimum block thickness 75 mm
- Maximum internal mould dimensions (1220 x 1220 mm)  
(subject to adjustments)
- Maximum block height 700 mm (subject to adjustments)

**Section 4: Technical Data**

**Powerage**

Tower 1	1.12 kW
Tower 2	4.73 kW
Tower 3	5.95 kW
Driving Chain	1.50 kW
Air compressor	6.00 kW
Additional	1.50 kW
<b>In total</b>	<b>20.80 kW</b>
Voltage	400 V, 50 Hz
Current	52,0 A
Tower quantity	1 x top and bottom cutter 2 x vertical cutter
Cutting speed:	subject to regulation through software
Capacity, min:	6 m <sup>3</sup> per hour
Capacity, max:	10 m <sup>3</sup> per hour
Effective capacity:	depends on numbers of vertical cuts
Rail system:	included
Sample mould:	included, 1set (1220x1220x700mm)
Storing / operating temperature:	+5°C to +60°C

**Section 5: Application**

The **LithoPore® Cutting Machine SM100** is only suitable for the cutting of wet LithoPore® Aerated Concrete – LPAC up to ~200 kPa of compressive strength.

### Section 6: Cutting Procedure

- The moulds have to be opened before cutting process begins
- The block is staying on the mould basement
- The block on mould basement will be placed on starting position.
- A chain will automatically bring the block to the first cutting position.
- Tower 1 for top and bottom cutting will drive automatically through the block.
- The block will be then transported automatically with the chain into Tower 2.
- The first vertical cut (longitudinal cutting) is done fully automatic (200mm or 150mm width)
- After the cut is finished the chain will bring the block automatically into Tower 3
- The vertical cut (transversal cutting) is done fully automatic (200mm or 150mm width)
- In case of need the tower can be automatically repositioned for 100mm or 75mm width
- The chain is pushing the block out of the cutting machine.
- Cut blocks have to be placed in further waiting area before final package
- 3 blocks can be cut simultaneously

---

The information contained in this product specification is based on our current state of knowledge and experience. It does not free the user from making his own tests and trial applications. A legally binding assurance of certain properties cannot be inferred from this information. Any existing patent rights as well as any pertinent legal regulations must be observed by the recipient of our products under his own responsibility.